



PART	MATERIAL
BODY	PTFE
PISTON	PTFE
END CAP	PVDF
DISK	PTFE
O-RINGS	VITON
SPRING	302 STAINLESS STEEL

O-RING	QTY
AS568A-018	4
AS568A-022	1
AS568A-124	1

SPECIFICATIONS	
DILUTION RATIO	2:1 TO 20:1
VACUUM RATING - MIN/MAX "HG	21/27
ACTUATOR PRESSURE - MIN/MAX PSIG (kPA)	40/60 (276/414)
CITY WATER PRESSURE - MIN/MAX PSIG (kPA)	30/60 (207/414)
MAX TEMPERATURE - MEDIA <sup>o</sup> F (°C)	302 (150)
MAX TEMPERATURE - AMBIENT <sup>o</sup> F (°C)	140 (60)

TOLERANCES UNLESS OTHERWISE SPECIFIED

ALL DIMENSIONS ARE IN INCHES

PATH =E:\CC\DYTEC\ADV-XX08P-TFE-V-SR.SLDRW

**DYTEC** 102 COMPASS PT. DR. STE. D.  
ST. CHARLES, MO. 63301-4414  
(636) 949-5600

ADV-XX08P-TFE-V-SR VALVE PHYSICAL DIMENSIONS

APPROVAL		DWN	MPJ	DATE 03/26/02	SCALE 1=1	CHRD
ENG	DATE	SZ				BY
GA	DATE	1 OF 1	44	0002355	30	00