



ASPIRATOR OPERATION NOTES
 1. USER MUST BE CAUTIOUS OF POTENTIAL CHEMICAL REACTIONS.
 2. VISCOSITY VARIATIONS IN FLUIDS BEING SIPHONED CAN CAUSE VARIATIONS IN PERFORMANCE.

SPECIFICATIONS	
VACUUM RATING - MIN/MAX INCHES OF Hg	5/18
DILUTION RATIO	1:1 TO 2.50:1
CITY WATER PRESSURE - MIN/MAX PSIG (kPa)	20/60 (138/414)
FLOW RATE - MIN/MAX GPM	1.0/4.0
MAX TEMPERATURE - MEDIA°F (°C)	302 (150)
MAX TEMPERATURE - AMBIENT°F (°C)	140 (60)

PART	MATERIAL
BODY	PTFE
DISK	PTFE
NOZZLE	PTFE

TOLERANCES UNLESS OTHERWISE SPECIFIED	DYTEC		102 COMPASS PT. DR. STE. D. ST. CHARLES, MO. 63301-4414 (636) 949-5600		
	ASL-0208P-TFE ASPIRATOR PHYSICAL DIMENSIONS				
APPROVAL		DWN BY	DATE	SCALE	CHRD BY
ENG	DATE	SHEET	MPJ	1=1	
ALL DIMENSIONS ARE IN INCHES		GA	DATE	1 OF 1	44
PATH = E:\CC\DYTEC\ASL-0208P-TFEP.SLDDRW					0002416 30 00